



May 20, 2010

Protect your workers with Safeguard® Technology Antislip Covers

Don't settle for temporary tapes and ineffective paints. Safeguard® Technology Antislip Covers provide a long-term solution to preventable slips-and-falls. Designed to retrofit over existing steps, ladders and walkways; Safeguard® Covers incorporate a hard, impact resistant aggregate and far exceed OSHA & ADA coefficient of friction standards even when wet or oily.



Benefit from easy installation with little to no downtime using either mechanical fasteners or adhesive. For more information and a Free Sample call (800) 989-1695.

Safeguard Technology, Inc.

[View Website](#)

Snap-In Flexible Connector Reduces Wear, Leaks & Saves Time

Connecting powder-processing equipment has never been more sanitary, safe or efficient. The BFM® fitting makes old-fashioned flexible sleeves fastened with hose clamps obsolete. They're perfect for vibrating and oscillating equipment, because they don't have crevices to trap material, or pinch points that cause wear. You can remove or replace the BFM fitting without tools. They always fit perfectly, no matter who installs them. Dust free. Explosion resistant. USDA approved. 3A certified. 877-BFM-FLEX (877-236-3539).



Powder-Solutions

[View Website](#)

How a Counter-Cyclonic Filter Works

Aerodyne "S" Series dust collectors use centrifugal force to efficiently separate out fine particles beginning at 20 microns... saw dust, fly ash, sand, coffee and many others.



Contact Aerodyne at 1-800-236-1506 or 1-440-543-7400. [Click here](#) to see animated demo of how cyclonic filtration works.

Aerodyne

[View Website](#)

New Product: A Speedy Feeder & Rapid Product Changeovers

According to Tecnet's Industries, the Tecweigh® QC10 single-drive feeder not only delivers the quickest way to empty a flexible hopper-style feeder, but also couples a unique Flex-Feed® polyurethane hopper featuring an opening in the bottom with the ability to agitate the hopper without driving the auger. When the material needs to be changed, simply stop the feeder and place a reclaim container underneath. Then open the bottom discharge slide gate and run the drive motor in reverse.



Tecnet's Industries

[View Website](#)

New Product: Tough Process Gauges

WIKA Instrument Corp. has released the XSEL process gauge, designed for pressure applications in refining, petrochemical and chemical plants. The XSEL features:



- A pressure system that can withstand harsh plant environments.
- Optional stainless steel, Monel and copper alloy.
- A stress-reducing Bourdon tube.
- The capability to produce 10 million or more pressure cycles.
- Resistance to vibration and pulsation, which helps to reduce downtime.

WIK A Instrument Corp.

[View Website](#)

New Product: A Dynamic Bulk Density Meter

3i's Technologies' BatchHouse™ meter is a real-time, in-line dynamic bulk density meter that provides:



- No interruption of the flow of material in the process.
- An output signal that represents the dynamic real-time bulk density of the solids material or mixture of materials being processed.
- Selection from feed-forward or feed-back mode.
- A bulk solids pump and a material hopper.

3i's Technologies Inc.

[View Website](#)

To ensure that you receive CHEM.INFO e-newsletters properly, please add the following domain to your e-mail "safe" list: [abc-media.com]

You are currently registered to receive CHEM.INFO Video & Product Showcase at [info@wika.com]

[Online Support Team](#) | [Unsubscribe](#) | [Subscribe](#) | [Privacy Policy](#)
[Subscribe/Renew to CHEM.INFO Magazine](#) | [Editorial Feedback](#)

CHEM.INFO

100 Enterprise Drive, Suite 600
Rockaway, NJ 07866-0912

©2010 CHEM.INFO. All Rights Reserved.